

**MARINE COATINGS  
TOPSIDE PAINT**

<b>DESCRIPTION</b>	An oil modified alkyd enamel for use above the waterline.
<b>APPEARANCE</b>	High Gloss and Semi-gloss
<b>PRODUCTS</b>	207005 Battleship Gray 207006 Black 207007 Deep Green 207002 Navy Blue 207004 Bright Red 207003 Sand Beige 207001 Oyster White 207000 Semi-Gloss White 206999 White
<b>RECOMMENDED PRIMERS</b>	207014 White Wood & Fiberglass Primer 207016 White Metal Primer
<b>PACKAGING</b>	Quarts
<b>PHYSICAL PROPERTIES</b>	
RESIN TYPE	Oil Modified Alkyd
SOLVENTS	Mineral Spirits
PRACTICAL COVERAGE	Approximately 100 sq. ft.
DRY TIMES @70°F (21°C) and 50% RH	
TOUCH	2-4 hours
HANDLE	4-7 hours
RECOAT	After 24 hours
SHELF LIFE	5 years
<b>SURFACE PREPARATION</b>	Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.  Remove all loose rust or deteriorated coatings by scraping or wire brush. For optimal results apply one coat of primer.
<b>APPLICATION</b>	Stir thoroughly. Thinning not needed for brush or roller. If sprayed, thin up to 15% with acetone. Apply with good quality brush, roller or spray gun.  May recoat when fully dry, usually in 24 hours.
<b>CLEAN-UP</b>	Clean brush, roller, and other tools with mineral spirits.