

VINYL Sprays

DESCRIPTION	A permanent, flexible coating to restore the color on vinyl, simulated leather and some fabrics.
APPEARANCE	Gloss tan, black and white finishes
PACKAGING	11 oz. can
RECOMMENDED PRIMER	None
SURFACE PREPARATION	Remove all dirt, grease, oil, salt or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. Use in properly ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray.
APPLICATION	Apply only when air and surface temperatures are between 50°-100°F (10°-38°C) and humidity is less than 85% to ensure proper drying.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Vinyl Resin.
SOLVENTS	Cyclohexanone, Acetone, Toluene, Isobutyl Acetate, Methyl Ethyl Ketone
VOLATILE ORGANIC COMPOUNDS	Maximum 60%
PRACTICAL COVERAGE	Approximately 6 to 7 sq. ft./can (.54-.63 M ² /can) @ RECOMMENDED DFT
DRY TIMES @ 70° (21°C) and 50% RH	Tack Free: 1 hour Handle: 1 – 2 hours Recoat: May recoat anytime. (Lower temperatures or higher humidity will extend dry times)
DRY HEAT RESISTANCE	200°F (93° C)
SHELF LIFE	5 Years