



STOPS RUST CHAIN LINK FENCE GALLON

DESCRIPTION AND USES

Rust-Oleum® Stops Rust® Chain Link Fence Paint is designed to protect and preserve weathered galvanized metal fences. It offers excellent coverage, chip resistance, and color retention. One coat will extend the life of the fence and restore and attractive appearance.

PRODUCTS

FINISHES

7787402 Metallic Silver

PRODUCT APPLICATION

SURFACE PREPARATION

Cut down weeds and long grass along the fence. Brush the wire mesh, posts and supports with a stiff broom to remove loose rust, dirt, etc. Hose down the fence with fresh water.

When the fence is dry, spot prime any rusted areas with Stops Rust® 7769 Rusty Metal Primer. Do not prime non-rusted areas.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. For additional information, contact the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Before using, stir thoroughly to ensure any settled pigment is re-dispersed. If necessary, thin the material with mineral spirits. For brush or roller, thin no more than 5% with mineral spirits. Do not thin with gasoline, lacquer thinner, turpentine, etc. Apply with a good quality brush and roller.

Apply only when air and surface temperatures are between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying.

Brush: Apply to fence posts and horizontal supports. Excessive brushing will reduce protection.

Roller: Use an extra long nap (1-1½ inch) lamb's wool roller which will reach around each individual wire and coat approximately 70% of the surface in a single pass. Paint at a 45° angle and cover about four strands at each pass. Move slowly and roll away from previously painted surfaces. Then work back in for a uniform appearance. A second painter with a similar roller lightly loaded with paint can follow on the other side to pick up excess paint and finish the process.

CLEAN-UP

Clean brush, roller, and tools with Mineral Spirits.



TECHNICAL DATA

STOPS RUST CHAIN LINK FENCE GALLON

PHYSICAL PROPERTIES

| | | METALLIC SILVER |
|--|-------------|--|
| Resin Type | | Oil modified Alkyd |
| Pigment Type | | Leafing Aluminum |
| Solvents | | Mineral Spirits |
| Weight | Per Gallon | 8.2 lbs. |
| | Per Liter | 0.98 kg |
| Solids | By Weight | 49.2% |
| | By Volume | 36.8% |
| Volatile Organic Compounds | | <500 g/l (4.2 lbs./gal.) |
| Recommended Dry Film Thickness (DFT) Per Coat | | — |
| Wet Film to Achieve DFT | | — |
| Theoretical Coverage at 1 mil DFT (25µ) | | — |
| Practical Coverage at Recommended DFT | | 240 sq.ft. /qt. Approximately 40 linear feet of six foot high fence |
| Dry Times at 77°F (25°C) and 50% Rel. Hum. | Touch | 2-4 hours |
| | Handle | 4-7 hours |
| | Recoat | 24 hours |
| Dry Heat Resistance | | — |
| Shelf Life | | 5 years |
| Safety Information | Flash Point | 104°F (40°C) |
| | Contains | — |
| | Warning! | FOR ADDITIONAL INFORMATION, SEE MSDS. |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.