



**STOPS RUST
TEXTURED SPRAYS**

DESCRIPTION AND USES

Rust-Oleum® Stops Rust® Textured Sprays are designed to provide a durable protective coating with excellent resistance to rust, and excellent resistance to abrasion, fading, chipping, and dulling. These sprays apply easily, provide excellent coverage and dry fast to a tough attractive finish. Rust-Oleum® Stops Rust® Textured Sprays are ideal for outdoor metal surfaces. These sprays feature a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and an any-angle tip which allow s you to spray at any angle. Not for use on galvanized metal.

PRODUCTS

MULTICOLOR TEXTURE

- 223523 Autumn Brown
- 223524 Desert Bisque
- 223525 Aged Iron
- 223526 Deep Forest
- 239119 Sea Green
- 239120 Radiant Brass
- 239121 Caribbean Sand
- 239122 Rustic Umber

TEXTURED METALLIC

- 251053 Silver
- 252303 Galaxy
- 252304 Moonlit Copper
- 262658 Excalibur
- 262660 Mystic Brown

TEXTURED

- 7220830 Black
- 7221830 Dark Pewter
- 7222830 Forest Green
- 7223830 Sandstone
- 7224830 Nickel
- 7225830 White
- 7226830 Bronze
- 7227830 Rust
- 7228830 Sage
- 241253 Dark Olive
- 241254 Dark Taupe
- 241255 Dark Brown
- 241256 Old Brick

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRIMING

Use of a Rust-Oleum® primer provides added corrosion protection, excellent adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended.

- 7769 Rusty Metal Primer
- 7780 Clean Metal Primer



TECHNICAL DATA

STOPS RUST TEXTURED SPRAYS

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes, dry to handle in 1-2 hours, and fully dry in 48 hours. Primers may be top coated immediately. Apply a second coat or clear coat within 1 hour or after 48 hours.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.



TECHNICAL DATA

STOPS RUST TEXTURED SPRAYS

PHYSICAL PROPERTIES

		FINISHES
Resin Type		Solvent Acrylic
Pigment Type		Varies with color
MIR		1.4 Max; 1.9 Max (metallic)
Fill Weight		12 ounces
Solvents		Acetone, Toluene, Xylene
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils
Practical Coverage at Recommended DFT (assumes 15% material loss)		10-12 sq. ft./can (0.9-1.09 m ² /can)
Dry Times at 77°F (25°C) and 50% Relative Humidity	Tack-free	15 minutes
	Handle	1-2 hours
	Recoat	Before 1 hour or after 48 hours
Dry Heat Resistance		200°F (94°C)
Shelf Life		5 years
Safety Information	Flash Point	-156°F (-144°C)
	Contains	Lead-free
	Warning!	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.