

PAINT DEGLOSSER

ELIMINATES SANDING – PREPS GLOSSY SURFACES FOR NEW FINISHES

Performance Characteristics:

- **WORKS ON** - Oil & Latex Paints, Enamels, Varnish and other finishes.
- **SAVES TIME** - Easier than sanding
- **INCREASES ADHESION** – Helps new paint bond to old finishes
- **CLEANS** - Removes dirt, stains, grease and wax



Product No.

42124

Recommended Uses:

Paints and clear finishes will not bond properly to glossy or dirty surfaces. **ZINSSER PAINT DEGLOSSER** eliminates sanding, helps new finishes bond to old, and cleans surface to minimize chipping, cracking and peeling between finishes. Works on all types of paints, enamels, varnishes and stains. Great for wood moldings, kitchen cabinets, door facing and more.

Application Data

Preparation – Spread a solvent resistant drop cloth covered in newspaper around work area in case of drips or spills. Protect eyes and skin, wear safety goggles and chemical resistant gloves. Shake before using, and open can carefully to relieve pressure. Use at temperatures above 65°F.

WARNING! If you scrape sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application Requirements

1. Saturate a clean, lint free cloth in **ZINSSER PAINT DEGLOSSER**
2. Wipe and clean surfaces completely by rubbing surface in circular motion. Fold and resaturate cloth frequently to prevent redepositing of soils.
3. Finish by brushing on a moderate coat of deglosser.
4. Allow surface to dry 30 minutes before applying a new finish. For best results apply new finish within one hour of using **ZINSSER PAINT DEGLOSSER**

NOTE – A white haze may appear when deglossing a previously finished clear coating. This is an indication that wax has not been completely removed. Repeat cleaning process until white haze disappears. Do not use on linoleum, asphalt, rubber tile, synthetic fabrics, plastics or recently repainted and refinished surfaces.

Clean up – Tools and brushes should be cleaned with soap and water immediately after use.

First Aid – In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. In case of skin contact, wash thoroughly with soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. If you experience difficulty breathing leave the area to obtain fresh air, if continued difficulty is experienced get medical attention immediately. If swallowed contact a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel.

Spillage – Open containers carefully and close after each use. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate then dispose of in a metal container.

Disposal – Call your local sanitation department for aid in disposing of unwanted product in your area or call the Environmental Protection Agency Solvent and Hazardous Waste hotline at 1-800-424-9345. Do not dump on the ground or in local sewer discharge system.

WARNING! – VAPORS MAY IGNITE EXPLOSIVELY. VAPORS MAY CAUSE FLASH FIRE. Contains Isopropanol, Petroleum Distillates and Toluene. Do not smoke. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, and turn off stoves heaters, electric motors and other sources of ignition during use and until all vapors are gone. **USE ONLY WITH ADEQUATE VENTILATION.** Prevent build-up of vapors by opening windows and doors to achieve cross ventilation. Vapor is harmful, it may affect the brain or nervous system causing dizziness, headache or nausea. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Causes eye, skin, nose and throat irritation. Do not get in eyes on skin or clothing. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm. Wash clothing before re-use. Thoroughly clean contaminated shoes. **KEEP OUT OF REACH OF CHILDREN.**

Specification Data

Temperature Range	Application	40°F. – 90°F.
Shelf Life		60 months @ 75°F.
VOC		100 %
Flash Point		60 ° F
Storage Condition		40°F. – 90°F.
Freeze/Thaw Stable		Yes

Packaging

Unit Size	Unit Code	Case Pack	Case Weight	Pallet Pack
1 quart	42124	6	27 lbs.	84 cases

Warranty:

This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have a question, check with your dealer or contact Rust-Oleum Corporation, Vernon Hills, IL. Warranty is limited to replacement or refunded value of product actually used if such product proves to be defective within two years of manufacture.

Technical Assistance - Available through local authorized Rust-Oleum dealers. For the dealer nearest you call 847-367-7700 or visit our website at www.zinsser.com.

Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

An RPM Company

Phone: 847•367•7700

www.rustoleum.com