

## WATERTITE™ HYDRAULIC CEMENT For Concrete & Masonry



10lbs.



2.5lbs.

### Description:

WATERTITE HYDRAULIC CEMENT is used to stop water flow and permanently seal deep cracks and holes in all grades of concrete. It plugs, seals and creates a “watertight” seal in 5 minutes, even while water is flowing. Also, use as anchoring cement. Use for interior and exterior surfaces.

### **Suitable Substrates:**

Concrete block, cast-in-place concrete, stucco, tilt-up, exposed aggregate, slump block

### **Suitable Uses:**

Basement & cellar walls, expansion and control joints, curtain wall joints, windows, doors, panels, fountains, reflecting pools, planters, canals, retaining walls, privacy fences

### **Features:**

- Plugs and seals deep holes in concrete and masonry
- Creates “watertight” seal in 5 minutes – even as water is flowing (stops active and non-active leaks)
- Use on interior and exterior concrete and masonry surfaces
- Can be used as an anchoring cement

### **Physical and Chemical Characteristics:**

Working time – 3 to 5 minutes

Setting time – 5 minutes

Final cure – 28 days

See MSDS sheet for particulars.

### **Directions for Use:**

Surface Preparation and Application - Chisel holes to enlarge them by at least ¼” and scrape clean. Remove any loose or chipped concrete. Make sure that the surface to be patched is damp. Mix two parts **WATERTITE HYDRAULIC CEMENT** to one part water. Stir the mixture until it reaches a putty-like paste. Mixture will begin to set in 3 to 5 minutes. Only mix as much material as you can use at one time. Hold mixture compound in gloved hand until it becomes warm. Force it firmly into the hole or crack and hold in place for 5 minutes. Immediately trim or brush away any excess cement for a smooth finish.

**Important:** Wear eye protection and rubber gloves when working with **WATERTITE HYDRAULIC CEMENT**.

### **For Best Results:**

- Always apply to a damp surface
- Apply from the top of the opening down
- Keep the patched area damp for several hours after the application
- If paint is desired, always use a good quality latex-based or masonry paint for a professional finish
- Always follow manufacturers application directions

Wash skin and hands with soap and water. Cured material must be scraped away.

**PACKAGING DATA**

| Code  | Package  | Case Amount | UPC              |
|-------|----------|-------------|------------------|
| 05071 | 10 lbs.  | 4           | 0 47719 050 71 1 |
| 05074 | 2.5 lbs. | 6           | 0 47719 05074 2  |

**FIRST AID – SAFETY INSTRUCTIONS:**

**WARNING!** Contains Portland Cement and Lime. Do not get in eyes. In case of eye contact flush eyes with water for at least 15 minutes and consult a physician immediately. Avoid contact with skin. Wear safety goggles and gloves to prevent eye and skin contact. Wash thoroughly after handling. Use only with adequate ventilation. Ensure good cross ventilation during application and drying. Do not breathe dust. To avoid dust exposure, wear an appropriate properly fitted (NIOSH approved) particulate respirator during mixing and sanding. Follow respirator manufacturer's directions for respirator use. If you experience difficulty in breathing, leave the area to obtain fresh air. If symptoms persist, get medical attention. Do not swallow. If swallowed, a physician or poison control center. **WARNING!** This product contains a chemical known to the state of California to cause cancer. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN.**

**WARRANTY:**

Limited Warranty - This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have a question, check with your dealer or contact Rust-Oleum Corporation. Warranty is limited to replacement or refunded value of product actually used if such product proves defective within two years of manufacture.

Manufactured and distributed by:  
ZINSSER Co. Inc.  
173 Belmont Dr.  
Somerset, NJ 08875  
732-469-8100

**Keep out of reach of children**

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

**Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061**

**An RPM Company**

**Phone: 847•367•7700**

**www.rustoleum.com**